

TECH SPECS SHOCKS

<i>Model</i>	<i>Weight [g] @ 165 mm e-t-e</i>	<i>Eye-to-eye x travel [mm]</i>	<i>Air chamber, finish</i>	<i>Spring system</i>	<i>Damping</i>	<i>Adjustments</i>	<i>Remote</i>	<i>Mounting system</i>	<i>Standard hardware sizes</i>
XR Carbon	142	165 x 37.5 190 x 50 200 x 50 200 x 55	Carbon fiber	ABS	Superlight, factory tuned hydraulic damping circuit lockout	Rebound Compression lockout	option	ball joint	22.2 / 25.4 x 6/8
XM 180	177	165 x 37.5 190 x 50 200 x 50 200 x 55	Aluminium black anodized	ABS	Superlight, factory tuned hydraulic damping circuit lockout	Rebound Compression lockout	option	ball joint	22.2 / 25.4 x 6/8
M212	198	165 x 37.5 190 x 50 200 x 50 200 x 55	Aluminium black anodized	ABS	HS & LS rebound HS & LS compression lockout	Rebound Compression lockout	n.a.	ball joint	22.2 / 25.4 x 6/8
M212 Remote	218 incl. Lever	165 x 37.5 190 x 50 200 x 50 200 x 55	Aluminium black anodized	ABS	HS & LS Rebound HS & LS Compression lockout	Rebound Compression lockout	standard	ball joint	22.2 / 25.4 x 6/8